

JOHANNESBURG

16 Pressburg Rd Founders View North Modderfontein 1645 P.O Box 259 Modderfontein 1645 Tel: (011) 553-3700 Fax: (011) 609-0354

DURBAN

10 Imola Place Westmead P.O Box 15159 Westmead 3608 Tel: (031) 792-4800 Fax: (031) 700-3800 **CAPE TOWN**

Unit 1 Oregan Park Jlg Avenue Montague Gardens P.O Box 37251 Chempet 7442 Tel: (021) 527-4020 Fax: (021) 551-4057

Lead Laundry and Catering (Pty) Ltd. Reg. No. 1999/011719/07

VAT Reg No. 4360182168 www.legd.co.zg

No of pages incl cover 12

Attention: MARK HILL

Address OPEN ARMS HOME FOR CHILDREN SOUTH AFRICA

> P.O. BOX 165 KOMGA

4950

SOUTH AFRICA

Tel No 073 411 6655

Fax Cell

E-Mail flatoutharold@yahoo.com 20 March 2017

Dear Mark

RE: QU9500570

Thank you for your enquiry. We have pleasure in submitting our Quotation No 9 500 570 together with the relevant product information.

Lead Laundry and Catering is a leader in the supply of commercial and industrial laundry and catering equipment to mines, hospitals, hotels, factories and other institutions throughout sub-Saharan Africa. We offer a comprehensive laundry and catering design service, equipment supply (including commissioning and installation), and full after-sales service with consistent spares back-up and availability. Our service is backed by some of South Africa's leading experts. We look forward to hearing from you and assure you of our continued interest and co-operation.

We also include critical information on a few key factors which distinguish us from our competition and which should influence every purchase decision.

Yours faithfully,

BRAAM VAN ROOYEN

SALES CONSULTANT (CAPE TOWN)

braamv@lead.co.za



Prices subject to availability and exchange rate fluctuation





Four (4) Speed Queen Model NF3J

x 9.5kg Free standing high speed extract soft mount microprocessor controlled(self heating) washer extractor. Suitable for 220 or 380 volt electricity supply.Machine dimensions: w x d x h683 mm x 711 mm x 1092 mmWeight: 113 kg

http://www.lead.co.za/laundry/commercial-laundry/washers/front-load-commercial-laundry-stacked-washerdryer/

Price R 25 900.00



Four (4) Speed Queen Model SDE807

x 8.2 kg Timer operated tumble dryer. Suitable for 220 volt electricity supply. Machine dimensions: (w x d x h). $683 \text{ mm} \times 711 \text{ mm} \times 1092 \text{ mm}$. Weight: 61 kg.

R 103 600.00

http://www.lead.co.za/laundry/commercial-laundry/tumble-driers/tumble-dryers/



One (1) Speed Queen Model SY105 EL

x $10.5\,kg$ Heavy duty industrial microprocessor controlled electric heated high speed extract (400 g) soft mount washer extractor. Suitable for 380 volt electricity supply. Machine Dimensions: w x d x h 795 mm x 795 mm x 1225 mm. Net Weight: 210 kg

prices subject to availability and exchange rate fluctuation

Total cost excludes delivery and commissioning



One (1) Speed Queen Model ST030OPT EL

x 15kg Heavy duty industrial microprocessor controlled tumble dryer with over-dry prevention technology. Suitable for 380 volt electricity supply. Machine dimensions: w x d x h711 mm x 1191 mm x 1622 mmNet Weight: 150 kg

http://www.lead.co.za/laundry/industrial-on-premise-laundry/tumble-driers-industrial-on-premise-laundry/industrial-on-premise-tumble-driers/



Two (2) Bluitalia Model GAMMA

Heavy duty 7 position height adjustable traditional ironing board (white) $1220 \times 400 \text{mm}$ with sleeve iron board, bottle and hanger support. Suitable for 220 Volt electricity supply. Dimensions $1220 \text{mm} \times 480 \text{mm} \times 1590 \text{mm}$ Weight: 9 kg

http://www.lead.co.za/laundry/auxiliary-equipment/ironing-boards-laundry-auxiliary/



2.2 Litre steam generator with iron. Dimensions: $395 \, \text{mm} \times 260 \, \text{mm} \times 175 \, \text{mm}$ HSuitable for 220 Volt electricity supply



http://www.lead.co.za/laundry/auxiliary-equipment/steam-hand-irons-laundry-auxiliary

Prices subject to availability and exchange rate fluctuation total cost excludes delivery and commissioning



Two (2) Lead Model SST1650X750

STAINLESS STEEL LAUNDRY FOLDING TABLE.plain top with stainless.steel legs for folding laundry.Dimensions: w x d x h.1650 mm x 750 mm x 910 mm.Weight: 34 kg.

http://www.lead.co.za/laundry/auxiliary-equipment/sst16502250-stainless-steel-folding-table/

Price R 4 590.00 R 9 180.00



ADAM 0-60 KG ELECTRONIC PLATFORM SCALE.SABS Approved.Pan size:400 mm x 500 mm.Overall dimensions: (wxdxh).860 x 400 x 620 mm.Net weight: 12.46 kg.

 $\label{limit} http://www.lead.co.za/laundry/auxilliary-equipment/lhs-50-laundry-hanging-scale-including-bag-and-bracket/$



 SubTotal
 R 286 170.00

 Delivery
 R 5 558.00

VAT @ 14% R 40 841.92

Total Cost R 332 569.92



Alternative Equipment



Four (4) Speed Queen Model SWNMN

x 7.2 kg Timer operated washer extractor. Suitable for 220 volt electricity supply.Machine dimensions: w x d x h.651 mm x 711 mm x 1092 mm. Weight: 86 kg.

http://www.lead.co.za/laundry/commercial-laundry/washers/top-load-washers/



Four (4) Speed Queen Model SDE807

 $x=8.2\,kg$ Timer operated tumble dryer. Suitable for 220 volt electricity supply. Machine dimensions: (w x d x h). 683 mm x 711 mm x 1092 mm. Weight: 61 kg.

http://www.lead.co.za/laundry/commercial-laundry/tumble-driers/tumble-dryers/



Four (4) Speed Queen Model NT3J

 $2 \times 9.5 \text{kg}$ Stacked combination unit comprising free standing high speed extract soft mount microprocessor controlled (self heating) washer extractor and 8kg tumble dryer. Suitable for 380 volt electricity supply. Machine dimensions: w x d x h683 mm x 711 mm x 1943 mmWeight: 168 kg

http://www.lead.co.za/laundry/commercial-laundry/stacked-washerdrier-combinations/stacked-washer-drier-combinations/

Alternative Equipment



Two (2) Sewoong Model PEN520

Hand held steam bottle Iron. Suitable for 220 Volt electricity supply. Machine dimensions: $w \times d \times h$ 280 mm \times 180 mm \times 320 mm Weight: 2.1 kg

http://www.lead.co.za/laundry/auxiliary-equipment/steam-hand-irons-laundry-auxiliary



One (1) Lead Model FIT

Mesh ironing table with padded ironing surface. Dimensions: w x d x h3100 mm x 800 mm x 820 mm (to work surface) Total height = 1970 mm

http://www.lead.co.za/laundry/auxiliary-equipment/ironing-boards-laundry-auxiliary/



One (1) Lead Model PLB50

Polyester laundry bag (blue) with trolley on castors. Dimensions: w x d x h 600mm \emptyset x 900mm Weight: 8.1 kg

http://www.lead.co.za/laundry/auxiliary-equipment/polyester-laundry-bag-trolley-on-castors/

Note: All alternative equipment excludes VAT, delivery and commissioning.

special Remarks

Delivery only, to be commissioned by Yates Electrical (Colin)

Based on:

100 Children Home

Washing Bedding and Clothing

Bedding is washed once per week

All single beds

2.5 kg per bed per change

Clothing washed once per week

Children range from baby to Matrix (grade 12)

5 kg per person per change

Laundry operates 8 hours per week

Laundry operates 7 days per week

Total required wash capacity - 15 kg per hour



specifications required

NF3J Speed Queen Model NF3J

Elect Conn: C1x30AMP SINGLE PHASE ISOLATOR 1600 MM A.F.F.L. (5.55kW)

OR 1 X 30AMP THREE PHASE ISOLA Connected Load: 5.55 kW (25.2AMPS) Electrical Usage: +/-1.46kW (40 MIN CYCLE)

Water Connection: 2X20MM TAPS (1 HOT & 1 COLD) 900MM A.F.F.L. Water USage: HOT=+/- 52 LITRES COLD=+/- 108 LITRES (40 MIN CYCLE)

Drain Conn: 1XDRAIN 50MM DIAMETER UPSTANDING BY 900MM AND LEADING INTO A COMMON

DRAIN 110MM

Detergent: +/-80GMS/CYCLE

Softner: +/- 80ML/CYCLE (TOWELS ONLY)

SDE807 Speed Queen Model SDE807

Electrical Connection: 1 X 30AMP SINGLE PHASE ISOLATOR 1000 MM A.F.F.L.

Connected Load: 5.6kW (24.8AMPS)
Electrical Usage: +/-3kW (45 MIN CYCLE)

Ducting: 100MM INTERNAL DIAMETER LEADING INTO COMMON DUCT OR GREATER OR THROUGH

AN EXTERIOR WALL Air Flow: 85 LITRES / SECOND

PLEASE NOTE: Machine is not supplied with an electrical power cable.

SY105 EL Speed Queen Model SY105 EL

Electrical Connection: 1X60AMP THREE PHASE ISOLATOR (5 WIRE) 1600 MM A.F.F.L.

Connected Load: 13.48kW(20.42AMPS)

Water Connection: 2X20MM TAPS (1 HOT & 1 COLD) 900MM A.F.F.L. Drain Connection: OPEN BOX GULLEY 300 MM SQUARE OR GREATER

ST030OPT EL Speed Queen Model ST030OPT EL

Electrical Connection: 1X60AMP THREE PHASE ISOLATOR (5 WIRE) 1600 MM A.F.F.L.

Connected Load: 24.2kW (36.67AMPS)
Electrical Usage: +/-9.7kW (30 MIN CYCLE)

Ducting: 150MM INTERNAL DIAMETER LEADING INTO COMMON DUCT OR GREATER OR THROUGH

AN EXTERIOR WALL

Air Flow: 203 LITRES / SECOND

MITO 3 Blultalia Model MITO 3

Electrical Connection: 1X15 AMP PLUG SOCKET 1000MM A.F.F.L.

Connected Load: 3.3kW (15AMPS)

GFK60M Adam Model GFK60M

SWNMN

Electrical Connection: 1X15AMP PLUG SOCKET

Speed Queen Model SWNMN

Electrical Connection: 1X15AMP PLUG SOCKET 1200MM A.F.F.L.

Connected Load: 0.375kW (1.8AMPS)

Electrical Usage: +/-0.22kW (35 MIN CYCLE)

Water Connection: 2X20MM TAPS (1 HOT & 1 COLD) 900MM A.F.F.L. Water Usage: HOT= +/- 56 LITRES COLD= +/- 64 LITRES (35 MIN CYCLE)

Drain Conn: 1XDRAIN 50MM DIAMETER UPSTANDING BY 1000MM AND LEADING INTO A COMMON

DRAIN 110MM DIA

Detergent: +/- 75GMS/CYCLE

Softener: +/- 75ML/CYCLE (TOWELS ONLY)

specifications required

SDE807 Speed Queen Model SDE807

Electrical Connection: 1 X 30AMP SINGLE PHASE ISOLATOR 1000 MM A.F.F.L.

Connected Load: 5.6kW (24.8AMPS)
Electrical Usage: +/-3kW (45 MIN CYCLE)

Ducting: 100MM INTERNAL DIAMETER LEADING INTO COMMON DUCT OR GREATER OR THROUGH

AN EXTERIOR WALL

Air Flow: 85 LITRES / SECOND

PLEASE NOTE: Machine is not supplied with an electrical power cable.

NT3J Speed Queen Model NT3J

Electrical Connection: 2x30AMP THREE PHASE ISOLATOR 1600 MM A.F.F.L.

Connected Load: Washer 5.55 kW (25.2AMPS); Dryer 5.6 kW

Electrical Usage: +/-1.46kW (40 MIN CYCLE)

Water Connectoin: 2X20MM TAPS (1 HOT & 1 COLD OR 2 X COLD) 900MM A.F.F.L.

Water Usage: HOT= +/- 52 LITRES COLD= +/- 108 LITRES (35 MIN CYCLE)

Drain Conn: 1XDRAIN 50MM DIAMETER UPSTANDING BY 900MM AND LEADING INTO A COMMON

DRAIN 110MM DIAMETER

Ducting: 100MM INTERNAL DIAMETER LEADING INTO COMMON DUCT OR GREATER OR THROUGH

AN EXTERIOR WALL.

Detergent: +/-80GMS/CYCLE

Softener: +/-80ML/CYCLE (TOWELS ONLY)

PEN520 Sewoong Model PEN520

Electrical Connection: 1 X 15AMP PLUG SOCKET 1000MM A.F.F.L.

Connected Load: 1kW (4.55AMPS)
Electrical Usage: +/- 0.8kWH



Basic terms and conditions

A full copy of our terms and conditions is available on request,.

Validity

• Prices are subject to change based on fluctuations in the exchange rate.

Availability

• Please check with your salesperson (serial equipment is generally ex-stock).

Installation

- Full instructions and specifications are available for your plumber and electricians upon request (refer warranty and detailed terms and conditions document).
- Should Lead Laundry and Catering (Pty) Ltd be contracted and undertake the delivery and commissioning of the equipment (extra cost), then all services are to be provided to within one metre of the machine. The cost of these services, inclusive of concrete plynths and ducting, is to be borne by yourselves. Any costs incurred in delivering equipment into position, where doorways, narrow passages or any form of other obstruction prevents easy access, will be for your account.

Additional Costs

• The cost of any additional mileage or labour as a result of these services not being available on the prearranged delivery and commissioning date is to be borne by yourselves, and will be invoiced directly by Lead Laundry and Catering (Pty) Ltd to yourselves, as will the cost of labour incurred in rectifying an inadequate floor, the relaying of reinforced flooring to meet the required specification and the cost of any additional mileage incurred for a second site visit (usually 21 days after relaying of the floor).

Terms of Payment

• Delivery will only take place after payment has been made in full. Normal cheque deposits require 10 working days before the funds are cleared in order for delivery to take place.

Warrantv

• Please note that terms and conditions apply to the warranty, a copy of which is available on request.

Speedqueen	3 years	Fagor	1 year	Jensen	1 Year
Tullis/Ipso	3 years	Sewoong	1 year drop off	llsa	1 Year
Girbau	3 years	Tullis (Grandimpianti/Image) 1 year		Sidi	1 Year

- Should the quotation contain any brands not mentioned above, please confirm the warranty period with the salesperson.
- Please consult your salesperson for recommended service and maintenance procedures. It is your responsibility to ensure the equipment is appropriately maintained. Any digression from the recommended service procedure which in our opinion results in machine failure may anull any or all equipment warranties.
- Warranties are applicable only in cases where machines (with outstanding warranties) have never been worked on, or where these machines have been previously worked on by Lead Laundry and Catering (Pty) Ltd and/or it's duly appointed and authorised agent. Warranties will immediately be rendered null and void in cases where equipment is operated on by anybody other than the abovementioned parties.
- Warranties are applicable only in cases where the equipment/machines are installed and commissioned by Lead Laundry and Catering (Pty) Ltd, and/or its duly appointed and authorised agent.
- Mileage and labour will be chargeable at all times (rates available on request). Parts under warranty that are faulty due to negligence, abuse, operator faults, etc. will be charged for.

Delivery

As specified in the quotation



Continued on next page

Basic terms and conditions

A full copy of our terms and conditions is available on request,.

Limitation of Liability

• Lead Laundry and Catering (Pty) Ltd does not accept responsibility for any consequential damages which may arise as a result of equipment failure or malfunction. Insofar as the delivery of goods is concerned, time shall not be of the essence of any contract of sale between Lead Laundry & Catering (Pty) Ltd and the customer, and any delivery or despatch dates mentioned in any quotation, order or other documentation emanating from Lead Laundry & Catering (Pty) Ltd shall be approximate only and shall not have any contractual effect on Lead Laundry & Catering (Pty) Ltd. In the event of any delay in delivery to the customer by Lead Laundry & Catering (Pty) Ltd and / or failure to effect delivery for any reason whatsoever other than a wilful breach by Lead Laundry & Catering (Pty) Ltd, then the customer shall not be entitled to cancel the contract, and shall have no claim for any loss or damages of whatsoever nature against Lead Laundry & Catering (Pty) Ltd as a result thereof.

SIZES, TOLERANCES, INSPECTION & SAMPLES: This quotation is made and based on the specifications provided either in writing or verbally by the customer (regardless of whether any samples are provided by the customer to Lead Laundry & Catering (Pty) Ltd). The dimensions for quoting and manufacturing are the mean specifications and are subject to the normal tolerances for variations

